



PRODUCT DATASHEET

LED Flood Light Stadium 300-1000 W 3000-6500 K

LL LED Professional Floodlight Stadium Light



AREAS OF APPLICATION

- Stadiums
- Pool Areas
- Public areas
- Building facades
- Construction areas
- Tennis Courts
- Football Courts

PRODUCT BENEFITS

- Highly efficient LED chip and high IP rating on luminaire front side
- Low maintenance and operation costs due to long lifetime of LED
- Energy savings up to 90% compared to Halogen Lamps
- Energy savings thanks to system efficiency of up to 140 lm/W
- Suitable for use in areas with high and low elevation ceilings

PRODUCT FEATURES

- Luminaire efficacy: up to 120-140 lm/W
- Symmetrical beam angle: 100° x 100°
- Mounting bracket for up to 180° tilting
- Type of protection: IP67
- Impact resistance: IK08
- Ambient temperature in operation: -20...+50 °C
- Connection via 1 m cable, wiring required



TECHNICAL DATA



Electrical data

Nominal wattage	300.00 W – 1000.00 W
Nominal voltage	220-240 VAC – Meanwell Driver
Power Factor	0.9
Mains Frequency	50 Hz

Photometrical data

Color temperature	3000 K - 6500 K
Luminous flux	36,000 lm – 140,000 lm
Luminous efficacy	120-140 lm/W
Standard deviation of color matching	≤5 sdcn
Light color (designation)	Warm White – Cool White - Day Light
Color rendering index Ra	80

Light technical data

Beam angle	24° - 100°
LED Brand	 OR 

Dimensions

Shape	Rectangle
-------	-----------

Colors & materials

Body material	Aluminum + Die-cast Iron
Housing color	White
Product color	White

Temperature & operating conditions

Ambient temperature range	-20°C ~ +50°C
---------------------------	---------------

Lifespan

Lifespan L70 at 25 °C	50,000 h
Number of switching cycles	100,000

Additional product data

Mounting type	Surface
Mounting location	Wall / Pole / Floor / Ceiling

Capabilities

Adjustable	Yes
Dimmable	No
Type of connection	Cable, 3-Pole
Technology	LED

Certificates & standards

Protection class	II
Type of protection	IP 67
Standards	CE/RoHS
