

# PRODUCT DATASHEET

## LED MINI SPOTLIGHT 7-9 W 4000 K

LUMBIENT LED MTF 6660



### AREAS OF APPLICATION

- Modern Workspaces
- Hotels
- High-End Villas
- Corridors
- Toilets

### TECHNICAL DATA

#### Electrical data

Nominal wattage	7-9 W
Nominal voltage	220-240 VAC
Power Factor	0.5/0.9
Mains Frequency	50-60 Hz

#### Photometrical data

LED Chip	OSRAM/PHILIPS/CREE/BRIDGELUX
Color temperature	4000 K
Luminous flux	600-900 lm
Luminous efficacy	80-100 lm/W
Standard deviation of color matching	≤3 sdc <sub>m</sub>
Light color (designation)	Natural White
Color rendering index Ra	90

#### Light technical data

Beam angle	15-40°
------------	--------

## Dimensions

Shape	Round
Dimensions	66 mm diameter – 60 mm height

## Colors & materials

Body material	Aluminum
Housing color	White-Black
Product color	White-Black

## Temperature & operating conditions

Ambient temperature range	-20°C ~ +60°C
---------------------------	---------------

## Lifespan

Lifespan L70 at 25 °C	50,000 h
Number of switching cycles	100,000

## Additional product data

Mounting type	Recessed
Mounting location	Ceiling

## Capabilities

Dimmable	No
Type of Connection	Screwless terminal, 2-Pole
Technology	LED

## Certificates & standards

Protection class	II
Type of protection	IP 20 / IP 44
Standards	CE/RoHS

