



PRODUCT DATASHEET

LED DOWNLIGHT DOUBLE 2x10 W 3000-6500 K

LUMBIENT LED Double Downlight Z-2P10



AREAS OF APPLICATION

- Showrooms
- Corridors
- Lobbies
- Bedrooms
- Living Rooms

TECHNICAL DATA

Electrical data

| | |
|-----------------|-------------|
| Nominal wattage | 2x10 W |
| Nominal voltage | 220-240 VAC |
| Power Factor | 0.9 |
| Mains Frequency | 50 Hz |

Photometrical data

| | |
|--------------------------------------|-------------------------------------|
| Color temperature | 3000 K - 6500 K |
| Luminous flux | 2,200 lm |
| Luminous efficacy | 110 lm/W |
| Standard deviation of color matching | ≤3 sdcn |
| Light color (designation) | Warm White – Cool White - Day Light |
| Color rendering index Ra | 90 |

Light technical data

| | |
|------------|--------|
| Beam angle | 24-60° |
|------------|--------|

Dimensions

| | |
|------------|-------------------|
| Shape | Rectangular |
| Dimensions | L110 mm x W200 mm |

Colors & materials

| | |
|---------------|-------------|
| Body material | Aluminum |
| Housing color | White-Black |
| Product color | White-Black |

Temperature & operating conditions

| | |
|---------------------------|---------------|
| Ambient temperature range | -20°C ~ +45°C |
|---------------------------|---------------|

Lifespan

| | |
|----------------------------|----------|
| Lifespan L70 at 25 °C | 50,000 h |
| Number of switching cycles | 100,000 |

Additional product data

| | |
|-------------------|----------|
| Mounting type | Recessed |
| Mounting location | Ceiling |

Capabilities

| | |
|--------------------|---------|
| Dimmable | No |
| Type of connection | L/N |
| Technology | LED COB |

Certificates & standards

| | |
|--------------------|-------------|
| Protection class | II |
| Type of protection | IP 65 |
| Standards | CE/RoHS/IES |

